



**SAFETY DATA SHEET  
ARDEX WPM 200 Part A**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME ARDEX WPM 200 Part A  
 APPLICATION Epoxide Primer Coating and Damp Proof Membrane.  
 SUPPLIER Ardex UK Limited  
 Homefield Road  
 Haverhill  
 Suffolk  
 CB9 8QP  
 Tel. 01440 714939  
 Fax. 01440 716667  
 CONTACT PERSON safetydatasheets@ardex.co.uk  
 EMERGENCY TELEPHONE +44 (0)870 190 6777 (24 hours)

**2 HAZARDS IDENTIFICATION**

CLASSIFICATION (1999/45) Xi;R36/38. R43. N;R51/53.  
 CLASSIFICATION (EC 1272/2008)  
 Physical and Chemical Hazards Not classified.  
 Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317  
 Environment Aquatic Chronic 2 - H411

LABEL IN ACCORDANCE WITH (EC) NO. 1272/2008



SIGNAL WORD Warning  
 CONTAINS Bisphenol F epichlorhydrin resin with MW <700  
 epoxy resin  
 Epoxy resin (average molecular weight <700)  
 OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS

HAZARD STATEMENTS  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P313 Get medical advice/attention.  
 P501 Dispose of contents/container to ...

SUPPLEMENTARY PRECAUTIONARY STATEMENTS  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P321 Specific treatment (see medical advice on this label).  
 P302+352 IF ON SKIN: Wash with plenty of soap and water.

**ARDEX WPM 200 Part A**

P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P337	If eye irritation persists:
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.

Supplemental Label Information (EU)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Bisphenol F epichlorhydrin resin with MW <700		1-3 %
CAS-No.: 28064-14-4	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xi;R36/38. N;R51/53. R43.	
DI-ISOBUTYL KETONE		< 1%
CAS-No.: 108-83-8	EC No.: 203-620-1	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 STOT SE 3 - H335	Classification (67/548/EEC) R10 Xi;R37	
epoxy resin		<15 %
CAS-No.: 55492-52-9	EC No.: 611-275-7	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xi;R36/38. N;R51/53. R43.	
Epoxy resin (average molecular weight <700)		15-30%
CAS-No.: 25068-38-6	EC No.: 500-033-5	Registration Number: 01-2119456619-26-xxxx
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R43 Xi;R36/38 N;R51/53	
LOW BOILING POINT NAPHTHA - UNSPECIFIED		< 1%
CAS-No.: 64742-95-6	EC No.: 265-199-0	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R10,R67,R66.	
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		<15 %
CAS-No.: 68609-97-2	EC No.:	Registration Number: 01-2119485289-22-xxxx
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Skin Sens. 1 - H317	Classification (67/548/EEC) R43 Xi;R38	

## ARDEX WPM 200 Part A

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

### 4 FIRST-AID MEASURES

**INHALATION**

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

**INGESTION**

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

**SKIN CONTACT**

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYE CONTACT**

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 6 ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Avoid discharge into drains, water courses or onto the ground.

**SPILL CLEAN UP METHODS**

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

### 7 HANDLING AND STORAGE

**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

**STORAGE CLASS**

Chemical storage.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
DI-ISOBUTYL KETONE	WEL	25 ppm	148 mg/m3			

WEL = Workplace Exposure Limit.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT**



**PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

**ARDEX WPM 200 Part A****HAND PROTECTION**

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

**EYE PROTECTION**

Wear tight-fitting goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid
COLOUR	Black.
ODOUR	Characteristic.
SOLUBILITY	Immiscible with water

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time.

**HAZARDOUS POLYMERISATION**

Will not polymerise.

**MATERIALS TO AVOID**

Strong oxidising substances.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**11 TOXICOLOGICAL INFORMATION****INHALATION**

Irritating to respiratory system.

**INGESTION**

May cause stomach pain or vomiting.

**SKIN CONTACT**

May cause sensitisation by skin contact. Irritating to skin.

**EYE CONTACT**

Irritating to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

**ARDEX WPM 200 Part A**

PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ), epoxy resin)
ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT	No.
UN NO. ROAD	3082
ADR CLASS NO.	9
ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III
HAZARD No. (ADR)	90
ADR LABEL NO.	9
HAZCHEM CODE	3Z
UN NO. SEA	3082
IMDG CLASS	9
IMDG PACK GR.	III
EMS	F-A, S-F
UN NO. AIR	3082
AIR CLASS	9
AIR PACK GR.	III

**15 REGULATORY INFORMATION**

## STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

## APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

## ISSUED BY

Research and Development Manager

REVISION DATE 26/04/2017

REV. NO./REPL. SDS GENERATED 5

## RISK PHRASES IN FULL

R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

## HAZARD STATEMENTS IN FULL

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

## ARDEX WPM 200 Part A

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.